DO NOT ENTER: /WK/ (10/17/2008)

Application No. 10/565,778

Reply to Office Action of August 14, 2008

IN THE CLAIMS

Please amend the claims as follows:

Claim 1 (Currently Amended): A disc eartridge recording and/or reproducing

apparatus comprising:

a disc; and

a disc cartridge having a main cartridge body unit configured to house said disc

therein and provided in at least one surface thereof with a recording and/or reproducing

aperture for exposing a part of said disc across inner and outer rims thereof;

wherein an opening for a driving unit, into which is intruded at least a part of

rotational driving means, configured for rotationally driving said disc, is formed in one

surface of said main cartridge body unit; the inner peripheral surface of said opening for the

driving unit operating as a mounting reference plane in a planar direction for mounting the

disc cartridge on a recording and/or reproducing apparatus; the peripheral edge of said

opening for the driving unit in said one surface operating as a mounting reference plane in the

height-wise direction for mounting the disc cartridge on the recording and/or reproducing

apparatus; and

an annular loading support part configured to position said disc cartridge in the

horizontal direction and in the height-wise direction, said loading support part having a ring-

shaped center fitting protrusion at an inner periphery fitted in said opening for a driving unit

of said disc cartridge.

Claim 2 (Original): The disc cartridge according to claim 1 wherein a lateral side of

said main cartridge body unit is formed as a substantially semicircular arcuate section having

the center of said disc housed in said main cartridge body unit as center.

2

DO NOT ENTER: /WK/ (10/17/2008)

Application No. 10/565,778

Reply to Office Action of August 14, 2008

Claim 3 (Original): The disc cartridge according to claim 2 wherein said arcuate

section is formed on a side of insertion of said main cartridge body unit into the recording

and/or reproducing apparatus.

Claim 4 (Previously Presented): The disc cartridge according to claim 3, wherein

said recording and/or reproducing aperture is formed facing a lateral side of said main

cartridge body unit other than the lateral side formed as said arcuate section.

Claim 5 (Original): The disc cartridge according to claim 1 further comprising:

a shutter unit configured to open/close said recording and/or reproducing aperture;

and

a slide guide formed on said main cartridge body unit for movably carrying said

shutter unit;

said slide guide being provided such that, when said inner peripheral surface is set on

said recording and/or reproducing apparatus, said mounting reference plane in said height-

wise direction is protruded from said slide guide towards said rotational driving means.

Claim 6 (Currently Amended): A disc recording and/or reproducing apparatus

comprising:

a cartridge holder on which is loaded a disc cartridge including a main cartridge body

unit, said main cartridge body unit rotatably housing an optical disc, said main cartridge body

unit being provided in at least one surface thereof with a recording and/or reproducing

aperture for exposing a part of said optical disc across inner and outer rims, there being

formed in one surface of said main cartridge body unit an opening, into which is intruded at

least a part of rotational driving means configured for rotationally driving said disc; the inner

3

DO NOT ENTER: /WK/ (10/17/2008)

Application No. 10/565,778

Reply to Office Action of August 14, 2008

peripheral surface of said opening operating as a mounting reference plane in a planar

direction for mounting the disc cartridge on a recording and/or reproducing apparatus; the

peripheral edge of said opening in said one surface operating as a mounting reference plane

in the height-wise direction;

an annular loading support part configured to position said disc cartridge in the

horizontal direction and in the height-wise direction; and

said annular loading support part having a ring-shaped center fitting protrusion at an

inner periphery, fitted in said opening for a driving unit of said disc cartridge, said annular

loading support part having a tapered surface support part at an outer periphery carrying the

peripheral edge of said opening for the driving unit of said disc cartridge.

Claim 7 (Previously Presented): The disc recording and/or reproducing apparatus

according to claim 6 wherein said loading support part is formed for surrounding the outer

rim of rotation driving means for rotationally driving said disc.

4